
Faneco 130° Angled Disabled Grab Bar, Ø 32 mm, Polished Stainless Steel

Code: S32UKS3SNP
EAN: 5901764295273





The Faneco 130° angled bathroom grab bar is designed for restrooms adapted to the needs of people with disabilities and users with limited mobility. The model is made of AISI 304 stainless steel with a polished finish, featuring a tube with a diameter of Ø32 mm and two arms, each 300 mm long. The two-point wall mounting system, secured with six screws, ensures a stable installation with a maximum load capacity of 120 kg.

Technical information

About the product

Product type	Angled grab bar
Category	Grab Bars
Brand	Faneco
EAN	5901764295273

Application

Intended use	Accessible bathrooms

Features and functions

Max. load (kg)	120.0 kg

Appearance and finish

Color	Steel
Handrail shape	Angled
Finish	Połysk

Materials

Material	AISI 304 stainless steel
Grab Bar Steel Thickness (mm)	1.5 mm
Rosette Steel Thickness (mm)	0.5 mm
Support Steel Thickness (mm)	3.0 mm
Steel joining	TIG welding

Dimensions and weight

Pipe diameter (mm)	32.0 mm

Height (mm)	287.0mm
Width (mm)	587.0
Depth (mm)	102.0mm
Vertical arm (mm)	300.0 mm
Horizontal arm (mm)	300.0 mm
Bend angle (°)	130.0 °
Support diameter (mm)	75.0 mm
Rosette diameter (mm)	76.0 mm
Weight (kg)	0.8 kg
Additional dimensions	Dimensions: 287 × 587 × 102 mm

Mounting and connections

Installation orientation	Vertical or horizontal
Fixing type	wall-mounted
Mounting method	Wall-mounted
Number of mounting points	6
Number of support points	2
Wall plug size (mm)	8mm x 50mm
Screw size (mm)	5mm x 60mm

Set contents

Wall plugs included	Yes
Screws included	Yes

Warranty

Warranty (years)	2
Warranty Type	door-to-door

Logistics – unit carton

Carton weight	1.0 kg

Description

A 130° angled wall grip designed for installation next to a toilet or shower, intended to provide stable support for people who need assistance when using the restroom.

The handrail is made of **AISI 304 stainless steel with a polished finish**. The tube has a diameter of Ø32 mm and a wall thickness of 1.5 mm. The steel components are joined using the TIG welding method.

- **Type: 130° angled handrail, 2-support**
- **Handrail length: 2 × 300 mm**
- **Material: AISI 304 stainless steel**
- **Finish: gloss**
- **Pipe diameter: Ø32 mm**
- **Pipe thickness: 1.5 mm**
- **Bracket diameter: Ø75 mm**
- **Bracket thickness: 3 mm**
- **Diameter of the cover plate: Ø76 mm**
- **Rosette thickness: 0.5 mm**
- **Bend angle: 130°**
- **Maximum load: 120 kg**
- **Number of support points: 2**

Product code: S32UKS3SNP
Faneco

- **Joining components: TIG welding**
- **Mounting: wall-mounted, 6-screw**
- **Overall dimensions: 287 × 587 × 102 mm**
- **Weight: 0.8 kg**

View product page
https://faneco.com/en/produkt/angled-grab-bar-for-disabled-faneco-130-32-mm-polished-steel-en/

Product code: S32UKS3SNP
Faneco