Faneco 6/4 Right-Hand Disabled Grab Bar, 90°, Ø 32 mm, White, Stainless Steel

Code: S32UKP64SWB
EAN: 5901764295181





The **Faneco 6/4 Right-Hand Angled Grab Bar** is designed for wall mounting next to a toilet, in a shower area, and in accessible washrooms for people with reduced mobility. Made of carbon steel with a white epoxy coating, it features a Ø32 mm tube and 600 mm and 400 mm arms. The three-point mounting system with nine screws ensures a secure and stable installation, with a maximum load capacity of 120 kg.

Technical information

About the product

Product type	Angled grab bar
Category	Grab Bars
Brand	Faneco
EAN	5901764295181

Features and functions

Max. load (kg)	120.0 kg

Appearance and finish

Color	White
Handrail shape	Angled
Orientation	Right
Coating	Farba epoksydowa
Coating thickness (µm)	70.0 µm

Materials

Material	Carbon steel
Grab Bar Steel Thickness (mm)	1.5 mm
Rosette Steel Thickness (mm)	0.5 mm
Support Steel Thickness (mm)	3.0 mm
Steel joining	TIG welding

Dimensions and weight

Pipe diameter (mm)	32.0 mm

Height (mm)	600.0mm
Width (mm)	400.0
Depth (mm)	102.0mm
Vertical arm (mm)	600.0 mm
Horizontal arm (mm)	400.0 mm
Bend angle (°)	90.0 °
Distance from wall (mm)	86.0 mm
Support diameter (mm)	75.0 mm
Rosette diameter (mm)	76.0 mm
Weight (kg)	1.5 kg
Additional dimensions	Dimensions: 600 × 400 × 102 mm

Mounting and connections

Installation orientation	Right-hand
Fixing type	wall-mounted
Mounting method	Wall-mounted
Number of mounting points	9
Number of support points	3
Wall plug size (mm)	8mm x 50mm
Screw size (mm)	5mm x 60mm

Set contents

Wall plugs included	Yes
Screws included	Yes

Warranty

Warranty (years)	2
Warranty Type	door-to-door

Logistics – unit carton

Carton weight	1.7 kg

Description

A wall-mounted angled grab bar designed primarily for installation in a shower area or next to a toilet, providing stable support for users of sanitary facilities.

The grab bar is made of **carbon steel with a white epoxy coating**. The tube has a diameter of Ø32 mm and a wall thickness of 1.5 mm. The steel components are joined using TIG welding.

- **Type: 90° angled grab bar, 3-point support**
- **Orientation: right-hand**
- **Vertical arm: 600 mm**
- **Horizontal arm: 400 mm**
- **Material: carbon steel**
- **Finish: white epoxy coating**
- **Tube diameter: Ø32 mm**
- **Tube wall thickness: 1.5 mm**
- **Mounting bracket diameter: Ø75 mm**
- **Mounting bracket thickness: 3 mm**
- **Cover plate diameter: Ø76 mm**

Product code: S32UKP64SWB
Faneco

- **Cover plate thickness: 0.5 mm**
- **Bend angle: 90°**
- **Maximum load: 120 kg**
- **Number of mounting points: 3**
- **Joining method: TIG welding**
- **Mounting: wall-mounted, 9 screws**
- **Overall dimensions: 600 × 400 × 102 mm**
- **Weight: 1.5 kg**

View product page
https://faneco.com/en/produkt/angled-grab-bar-for-disabled-faneco-6-4-prawa-90-32-mm-white-stal-en/

Product code: S32UKP64SWB
Faneco