Faneco Flush-Mounted Vanity Frame with Brackets

Code: KKU705
EAN: 5901764292708





Faneco flush-mounted sink frame with brackets, made of 1.5 mm thick powder-coated steel. Equipped with a metal connection plate and two G 1/2″ brass connectors. Mounted at two points to the wall and two points to the floor. Designed for installing a sink in a drywall structure.

Technical information

About the product

Product type	Washbasin frame
Category	Flush-mounted frames
Brand	Faneco
EAN	5901764292708

Application

Intended use	for hanging a washbasin in a plasterboard construction

Appearance and finish

Finish	Powder coating

Materials

Material	Powder-coated steel
Material thickness	1,5 mm

Dimensions and weight

Height (mm)	1120 - 1290 mm
Width (mm)	410
Depth (mm)	155 - 235 mm
Weight (kg)	9,7 kg

Mounting and connections

Mounting method	flush-mounted (2 fixing points to the wall, 2 fixing points to the floor)

Set contents

Installation kit	Yes
Set contents	Metal Connection Plate two brass connectors G 1/2''

Warranty

Warranty (years)	2
Warranty Type	door-to-door

Description

The Faneco flush-mount frame is **a steel mounting structure designed for suspending a sink in a drywall enclosure**. It allows for secure mounting of the sink and the installation of water connections inside the wall, ensuring that the plumbing components remain hidden behind the finished wall.

The adjustable height and depth of the frame allow you to adapt its configuration to the installation conditions and the intended height of the sink.

- **For wall-mounted sinks** —designed for in-wall installation of the sink.
- **For drywall installation** —a structure designed for installation in a lightweight framing system.
- **Powder-coated steel** – a durable structure protected by a coating.
- **The steel is 1.5 mm thick** —ensuring adequate frame rigidity.
- **4 mounting points** —2 on the wall and 2 on the floor—ensure that the structure is securely anchored.
- **Adjustable height: 1,120–1,290 mm** —allows the frame to be adapted to the planned installation.
- **Adjustable depth: 155–235 mm** —allows the unit to be adapted to the available installation space.
- **Width: 410 mm** —an important factor to consider when planning the layout.
- **Metal connection plate** – a structural component used to prepare the installation for a sink.
- **Two G 1/2" brass fittings included in the set** —for connecting hot and cold water lines.
- **Frame weight: 9.7 kg**.
- **Product code: KKU705**.
- **Warranty: 2 years door-to-door**.

The KKU705 frame allows you to create a stable, concealed structure for installing a wall-hung sink in a drywall enclosure. Height and depth adjustments make it easy to adapt the frame to a specific project, and two G 1/2" connections allow you to set up hot and cold water supply lines.

View product page
https://faneco.com/en/produkt/faneco-concealed-washbasin-frame-with-support-brackets/